

RANGE OF APPLICATION

DUMB WAITER NANO

version 2.0 / 26-04-2012

Factory – Head Office

Polykastro Industrial Park
61200 Polykastro, Greece
Tel.: +30 23430 20140, 20150
Fax: +30 23430 23701

Athens Office-Showroom

12, Lassani str., 12132
Peristeri, Athens, Greece
Tel.: +30 210 3416210, 210 5789881
Fax: +30 210 3416474

Athens Warehouse

Odyssea Eliti 98, Ano Liosia,
13342 Attiki, Athens, Greece
Tel.: +30 210 5595163,
Fax: +30 210 5596651

web: www.doppler.gr
Email: info@doppler.gr




DUMB WAITER nano

Range of Application

INDEX

3-D LAYOUT	3
TECHNICAL SPECIFICATIONS	4
LAYOUT ARRANGEMENT:.....	5
SINGLE ENTRANCE –GUIDE RAILS AT THE REAR.....	5
PLAN VIEW.....	5
LAYOUT ARRANGEMENT:.....	6
SINGLE ENTRANCE – GUIDE RAILS AT THE SIDE	6
PLAN VIEW.....	6
LAYOUT ARRANGEMENT:.....	7
THROUGH CAR – GUIDE RAILS AT THE SIDE	7
PLAN VIEW.....	7
LAYOUT ARRANGEMENT:.....	8
SINGLE ENTRANCE – GUIDE RAILS AT THE REAR (WITH METAL SHAFT).....	8
PLAN VIEW.....	8
LAYOUT ARRANGEMENT:.....	9
SINGLE ENTRANCE – GUIDE RAILS AT THE SIDE (WITH METAL SHAFT)	9
PLAN VIEW.....	9
LAYOUT ARRANGEMENT:.....	10
THROUGH CAR – GUIDE RAILS AT THE SIDE (WITH METAL SHAFT)	10
<i>Plan View.....</i>	<i>10</i>
LAYOUT ARRANGEMENT:.....	11
SHAFT GENERAL SECTION VIEW	11

3-D Layout



1.	CAR SLING
2.	METAL SHAFT
3.	COUNTERWEIGHT FRAME
4.	CAR GUIDES
5.	GUIDE BRACKETS
6.	COUNTERWEIGHT GUIDES
7.	MOTOR BASE
8.	SHAFT WALL
9.	MOTOR
10.	WIRE ROPES
11.	LANDING DOORS

Technical Specifications


Type	DUMB WAITER
Nominal Load:	250/300 Kg
Suspension:	1:1
Maximum Travel:	15000 mm
Suspended Load (P + Q)max	400/450 Kg
Minimum Headroom: (Typical)	2600mm (2800mm with safety gear) Serving Height (800mm)+ Cabin Height (1000mm)+ Shaft components height (800mm without safety gear/1000mm with safety gear DISG220)
Minimum Pit Depth + Serving Height:	Door Height / 2 + 200 mm*
Car Guides:	T70x65x9
Counterweight Guides:	T50x50x5
Car DBG:	850mm-950mm
Counterweight DBG:	Car DBG – 320mm
Motor type:	WORMGEARED MOTOR
Motor wattage: VVVF	1.5 kW
Minimum operating temperature:	- 30° C (ESSO-S220, MOBIL-Glycoil 30, SHELL-Tivela Oil WB, BP-Energol SG-XP 220, Texaco-B16Synoil CPL-220)
Controller's Minimum operating temperature:	-10° C
Sheave:	Ø200 mm
Nominal Speed:	0,5 m/s (VVVF)
Wire Ropes:	2xØ6 mm
Buffer:	ACLA Ø80x80mm
Safety Gear:	DISG 220

* Only for vertical sliding doors

Layout arrangement:

Single entrance –Guide rails at the rear

Plan view




DOOR POSITION A (DOOR AT FRONT)							
MODEL	CABIN			SHAFT		DOOR	
RATED LOAD 250/300KG	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	WIDTH	HEIGHT
	CW	CD	CH	SW	SD	DW	DH
NANO A	900-1000	550-1000	1000-1200	CW+200	CD+250	CW	CH

Layout arrangement:

Single entrance – Guide rails at the side

Plan view




DOOR POSITION B (SINGLE SIDE)							
MODEL	CABIN			SHAFT		DOOR	
RATED LOAD 250/300KG	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	WIDTH	HEIGHT
	CW	CD	CH	SW	SD	DW	DH
NANO B	550-1000	900-1000	1000-1200	CW+300	CD+150	CW	CH

Layout arrangement:

Through Car – Guide rails at the side

Plan view




DOOR POSITION B-B' (THROUGH CAR)							
MODEL	CABIN			SHAFT		DOOR	
RATED LOAD 250/300KG	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	WIDTH	HEIGHT
	CW	CD	CH	SW	SD	DW	DH
NANO B-B'	550-1000	900-1000	1000-1200	CW+300	CD+100	CW	CH

Layout arrangement:

Single entrance – Guide rails at the rear (With metal shaft)

Plan View




DOOR POSITION A (DOOR AT FRONT)							
MODEL	CABIN			SHAFT		DOOR	
RATED LOAD 250/300KG	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	WIDTH	HEIGHT
	CW	CD	CH	SW	SD	DW	DH
NANO A	900-1000	550-1000	1000-1200	CW+300	CD+350	CW	CH

Layout arrangement:

Single entrance – Guide rails at the side (With metal shaft)

Plan View




DOOR POSITION B (SINGLE SIDE)							
MODEL	CABIN			SHAFT		DOOR	
RATED LOAD 250/300KG	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	WIDTH	HEIGHT
	CW	CD	CH	SW	SD	DW	DH
NANO B	550-1000	900-1000	1000-1200	CW+400	CD+250	CW	CH

Layout arrangement:


Through Car – Guide rails at the side (With metal shaft)

Plan View



DOOR POSITION B-B' (THROUGH CAR)							
MODEL	CABIN			SHAFT		DOOR	
RATED LOAD 250/300KG	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	WIDTH	HEIGHT
	CW	CD	CH	SW	SD	DW	DH
NANO B-B'	550-1000	900-1000	1000-1200	CW+400	CD+200	CW	CH

Layout arrangement: Shaft General Section View



HDR	HEADROOM	TH+CH+800 mm(min)
UOT	UPPER OVERTRAVEL	100 mm(min)
T	TRAVEL	15000 mm(max)
PD + TH	PIT DEPTH + SERVING HEIGHT	DH/2+200 mm(min)
DOT	DOWN OVERTRAVEL	100 mm(min)